Line 4, delete "that"; and

Line 4, delete "leads" and insert --may lead--.

On Page 12, Line 6, delete "superposed" and insert --superimposed--.

On Page 13, Line 27, delete "it".

On Page 16, Line 26, delete "is" and insert --are--.

On Page 19, Line 18, after "and" insert --to--.

On Page 21, Line 3, delete "means" and insert --unit--.

On Page 23, Line 12, delete "a defective" and insert --any defects--;

Line 17, delete "reality" and insert --reliability--;

Line 20, delete "at" and insert --in--;

Line 28, delete "means" and insert --unit--; and

Line 30, delete "means" and insert --unit--.

IN THE CLAIMS

In Claim 3, Line 1, delete "or"; and

Line 2, delete "2".

In Claim 9, Line 2, delete "or 6".

In Claim 10, Line 2, delete "or 7".

Please add the following newly drafted Claims 18-23.

18. An arm for an elastic doll as defined in claim 2, wherein said core is formed thereon with a detachment-preventing section for preventing detachment of said spacer therefrom.

19. A method for molding an arm or arms for an elastic doll as defined in claim 6, wherein the shoulder of the arm is provided with an engagement groove adapted to be engaged with a trunk of a doll;

further comprising the step of arranging a support rod at a site in said molding space corresponding to said engagement groove, said support rod functioning to support said core against an injection pressure of a molding material during molding of the arm.

20. A method for molding arms for an elastic doll as defined in claim 7, further comprising the steps of:

separating said mold members from each other after molding of the arms; and

removing a portion of the core exposed from the shoulder of each of the arms.

21. A molded appendage for a doll, comprising:

an elongated core member that is bendable;

a spacer member connected to the core member and extending outward therefrom; and

an outer housing of a moldable resin material having an exterior surface to simulate the desired configuration of the appendage, the outer housing substantially encapsulating the core member and spacer member, the spacer member being integrated into the resin material of the outer housing.

22. The molded appendage of claim 21 wherein the spacer member is a resin material having a melting point equal to or below a melting point of the outer housing.

23. The molded appendage of claim 22 wherein the spacer member is appended at one end of the elongated core member and includes a plurality of outward projections.